



UPPER FORK

CPCD25T-SJ6

2.5T ELECTRIC FORKLIFT



Wide-view mast design and downward-moving cab instrument panel increase the driver's operating field of vision by 30% and improve safety



LED lamps, energy saving, long life, high brightness.



USA Cascade slider, lifetime warranty.



All models are equipped with Toyota intelligent comfort seats and enlarged and thickened engine hood as standard



Independently developed and produced integral casting counterweight, which is more than at least 100KG heavier than other competitors, maintaining value and more stable



Standard high-power AC motor, strong power





UPPER FORK

PARAMETERS &
PERFORMANCE

CPCD25T-SJ6

General

Manufacturer		SHANGCHA
Model		CPCD25T-SJ6
Power Type		Lithium battery
Rated Load Capacity	Q(kg)	2500
Load Centre	C(mm)	500

Characteristic & Dimension

Rated Lift Height	H3(mm)	3000
Free Lift Height	H2(mm)	150
Mast Tilt Angle (F/R, α°/β°)	°	6°/12°
Travel Speed (Full Load/No Load)	km/h	14.5/15
Lifting Speed (Full Load/No Load)	mm/s	350/480
Max.Gradeability(No Load/Full Load)	%	25/20
Turning Radius	Wa(mm)	2020
Total weight	kg	3900
Wheelbase	Y(mm)	1430
Fork Size (LxWxT)	mm	1070×120×40
Fork Overhang	X1(mm)	470
Front Track Width	B2(mm)	980
Rear Track Width	B3(mm)	970
Length to Face of Fork (Without Fork)	L1(mm)	2310
Overall Width	B1(mm)	1170
Mast Lowered Height	H1(mm)	2055
Overhead Guard Height	H5(mm)	2180

Power & Transmission

Battery	V/Ah	80/300
Drive Motor	kw	10
Lift Motor	kw	16
Service brake		Hydraulic pressure
Parking brake		Machinery
Operating Pressure (For Attachments)	Mpa	18.5
Controller		SANTROLL
Control mode		MOS/AC

Chassis

Tire		Pneumatic tire
Tyre (Front x 2)		7.00-12-12PR
Tyre (Rear x 2)		18×7-8-14PR

